



ROLADA EN CALIENTE

PESO POR HOJA DE LAMINA NEGRA

CAL.	PULG.	MM.	3'X6'	3'X8'	3'X10'	4'X8'	4'X'10'	KG./M.2
3	0.239	6.07	6.07	106.22	132.78	141.63	177.04	47.61
4	0.224	5.69	5.69	99.55	124.44	132.74	165.92	44.62
5	0.209	5.31	5.31	92.89	116.11	123.85	154.81	41.63
6	0.194	4.93	4.93	86.22	107.78	114.96	143.70	38.65
7	0.179	4.55	4.55	79.56	99.44	106.07	132.59	35.66
8	0.164	4.18	4.18	73.07	91.33	97.42	121.78	32.75
9	0.150	3.80	3.80	66.44	83.06	88.59	110.74	29.78
10	0.135	3.42	3.42	59.78	74.72	79.70	99.63	26.79
1/8	0.125	3.18	3.18	55.56	69.44	74.70	92.59	24.90
11	0.120	3.04	3.04	53.16	66.44	70.87	88.59	23.82
12	0.105	2.66	2.66	46.49	58.11	61.98	77.48	20.84
13	0.090	2.28	2.28	39.87	49.83	53.16	66.44	17.87
14	0.075	1.90	1.90	33.20	41.50	44.27	55.33	14.88
15	0.067	1.71	1.71	29.91	37.39	39.88	49.85	13.41
16	0.060	1.52	1.52	26.58	33.22	35.44	44.30	11.91
17	0.054	1.37	1.37	23.91	29.89	31.88	39.85	10.72
18	0.048	1.21	1.21	21.24	26.56	28.33	35.41	9.52